



### 2205 E-2RS1KTN9

# Self-aligning ball bearing with tapered bore and seals on both sides

Self-aligning ball bearings, with a tapered bore and seals on both sides, have two rows of balls, a common sphered raceway in the outer ring and two deep uninterrupted raceway grooves in the inner ring. They are insensitive to angular misalignment of the shaft relative to the housing. The tapered bore facilitates ease of mounting via adapter/withdrawal sleeves. The integral sealing can prolong bearing service life by keeping lubricant in the bearings and contaminants out.

- Ease of mounting via adapter/withdrawal sleeves
- Accommodate static and dynamic misalignment
- Excellent high-speed and light load performance
- Low friction
- Integral sealing results in reduced maintenance requirements and prolonged bearing service life

### Overview

#### **Dimensions**

Bore diameter	25 mm
Outside diameter	52 mm
Width	18 mm

#### Performance

Basic dynamic load rating	14.3 kN
Basic static load rating	4 kN
Reference speed	26 000 r/min
Limiting speed	9 000 r/min

### **Properties**

Retaining feature, inner ring	None
Locating feature, bearing outer ring	None
Number of rows	2
Bore type	Tapered 1:12
Cage	Non-metallic
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease




Relubrication feature

Without




## Technical Specification

Bore type	Tapered 1:12
-----------	--------------



### Dimensions

d	25 mm	Bore diameter
D	52 mm	Outside diameter
В	18 mm	Width
$d_2$	≈ 31 mm	Recess diameter inner ring
$D_2$	≈ 46.21 mm	Recess diameter outer ring
r <sub>1,2</sub>	min. 1 mm	Chamfer dimension



### Abutment dimensions

D <sub>a</sub>	max. 46.4 mm	Abutment diameter housing
ra	max. 1 mm	Fillet radius

### Calculation data

Basic dynamic load rating	С	14.3 kN
Basic static load rating	$C_0$	4 kN
Fatigue load limit	$P_{u}$	0.204 kN
Reference speed		26 000 r/min



Limiting speed		9 000 r/min
Permissible angular misalignment	α	1.5 °
Calculation factor	k <sub>r</sub>	0.045
Limiting value	е	0.28
Calculation factor	$Y_0$	2.5
Calculation factor	$Y_1$	2.2
Calculation factor	Y <sub>2</sub>	3.5

### Mass

Mass bearing	0.16 kg
--------------	---------



### Terms and conditions

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) ("SKF"), you agree to the following terms and conditions:

### Warranty Disclaimer and Limitation of Liability

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app. Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service. Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

### Third Party Services

When viewing YouTube content via the SKF website(s) (i.e. using YouTube API Services), you agree to be bound by the YouTube Terms of Service.

### Copyright

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third

This website /app includes certain images used under license from Shutterstock, Inc.

#### Trademarks and Patents

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

#### Changes

SKF reserves the right to make changes or additions to this website / app at any time.